MiniGrip Radio Remote Control



System Part Number: UBRF-MG-10

Radio Remote Control System consisting of MiniGrip Radio Transmitter & DC10 Radio Receiver Unit with N/O Momentary Relay Outputs.

Standard System Package: (customised label options available for MiniGrip Transmitter to include button functions and company logo)

1 x UBRF-MG-10 includes:



UB/RX/DC10/401



Part Numbers:

| UBRF-MG-10 | MiniGrip Radio Remote Control System | |
|-----------------------|--------------------------------------|--|
| UB/MG410 | MiniGrip Radio Transmitter | |
| <u>UB/RX/DC10/401</u> | DC4 Radio Receiver Unit | |

Optional Accessories:

| PA08/MG/002 | Belt Clip for MiniGrip Transmitter | |
|-------------|--------------------------------------|--|
| PA08/MG/003 | Wall Holder for MiniGrip Transmitter | |



Technical Specifications

MiniGrip Transmitter

| Number of buttons: | 7 |
|---------------------------------|--------------------|
| Battery type: | 2 x AAA |
| Dimensions: | 145 x 65 x 30mm |
| Weight: | 150g |
| IP Protection rating: | IP55 |
| Operating temperature: | -20 °C to +55 °C |
| Transport/storage temperature: | -40 °C to +70 °C |
| Antenna: | Internal |
| Operating distance range: | Up to 150 metres |
| Operating radio frequency band: | 433.075-434.775MHz |

DC10 Receiver Unit

| Power supply: | 12-24 VDC |
|---------------------------------|--|
| Outputs: | 10 |
| Max voltage to contacts: | 12A @ 250VAC & 24VDC |
| Dimensions: | 145.0 x 91.36 x 55.0mm |
| IP protection rating: | IP65 |
| Operating temperature: | -20 °C to +55 °C |
| Transport/storage temperature: | -40 °C to +70 °C |
| Antenna: | External Antenna on 3 metre cable (pre-fitted) |
| Operating radio frequency band: | 433.075-434.775MHz |



