





ProGrip18 InfraRed Remote Control

	<p>System Part Number: UBIR-PG18-26</p> <p>InfraRed Remote Control System consisting of ProGrip18 IR Transmitter & DC26 IR Receiver Unit with N/O Momentary Relay Outputs. AC Transmitter Charger included.</p>
---	--

Standard System Package: (Customised label options available for ProGrip Transmitter to include button functions and company logo. Protective Bumper can also be supplied in Yellow, Green or Grey)

1 x UBIR-PG18-26 includes:

<p>UB/PRO18/IR/TX01</p> 	<p>UB/RX/DC26/IR01</p> 	<p>PA31/CHARGER/01</p> 
---	---	--

Part Numbers:

<u>UBIR-PG18-26</u>	ProGrip18 IR Remote Control System	
<u>UB/PRO18/IR/TX01</u>	ProGrip18 IR Transmitter	
<u>PA31/CHARGER/01</u>	AC Transmitter Charger (DC optional)	
<u>UB/RX/DC26/IR01</u>	DC26 IR Receiver Unit	

Optional Accessories:

<u>PA31/CHARGER/02</u>	DC Transmitter Charger	
<u>PA08/BOP/005</u>	Lanyard Loop & Lanyard for ProGrip	
<u>PA08/BOP/006</u>	Universal Belt-Clip for ProGrip	
<u>PA08/BOP/013</u>	Wall Holder for ProGrip	

Technical Specifications

ProGrip18 IR Transmitter

Number of buttons:	18
Battery type:	4 x AA (Rechargeable LiPo)
Dimensions:	209.3 x 98.0 x 34.8mm
Weight:	320g
IP Protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	N/A
Operating distance range:	Up to 30 metres line-of-sight
Operating InfraRed frequency band:	36KHz PWM InfraRed

DC26 IR Receiver Unit

Power supply:	12-24 VDC
Outputs:	26
Max voltage to contacts:	<ul style="list-style-type: none">• 18 x General Purpose Relays (5A @24VDC)• 2 x Stop Relays (8A @24VDC)• 6 x General Purpose Relays (12A @24VDC)
Dimensions:	252.0 x 147.4 x 55.0mm
IP protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	N/A
Operating InfraRed frequency band:	36KHz PWM InfraRed

