





ProGrip21 Radio Remote Control

	<p>System Part Number: UBRF-PG21-26</p> <p>Radio Remote Control System consisting of ProGrip21 Radio Transmitter & DC26 Radio Receiver Unit with N/O Momentary Relay Outputs.</p> <p>AC Transmitter Charger included.</p>
---	--

Standard System Package: (Customised label options available for ProGrip Transmitter to include button functions and company logo. Protective Bumper can also be supplied in Yellow, Green or Grey)

1 x UBRF-PG21-26 includes;

<p>UB/PRO21/433/TX01</p> 	<p>UB/RX/DC26/401</p> 	<p>PA31/CHARGER/01</p> 
--	--	--

Part Numbers:

<u>UBRF-PG21-26</u>	ProGrip21 Radio Remote Control System	
<u>UB/PRO21/433/TX01</u>	ProGrip21 Radio Transmitter	
<u>PA31/CHARGER/01</u>	AC Transmitter Charger (DC optional)	
<u>UB/RX/DC26/401</u>	DC26 Radio Receiver Unit	

Optional Accessories:

<u>PA31/CHARGER/02</u>	DC Transmitter Charger	
<u>PA08/BOP/005</u>	Lanyard Loop & Lanyard for ProGrip	
<u>PA08/BOP/006</u>	Universal Belt-Clip for ProGrip	
<u>PA08/BOP/013</u>	Wall Holder for ProGrip	

Technical Specifications

ProGrip21 Radio Transmitter

Number of buttons:	21
Battery type:	4 x AA (Rechargeable LiPo)
Dimensions:	209.3 x 98.0 x 34.8mm
Weight:	320g
IP Protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	Internal
Operating distance range:	Up to 150 metres
Operating radio frequency band:	433.075-434.775MHz

DC26 Radio Receiver Unit

Power supply:	12-24 VDC
Outputs:	26
Max voltage to contacts:	<ul style="list-style-type: none">• 18 x General Purpose Relays (5A @24VDC)• 2 x Stop Relays (8A @24VDC)• 6 x General Purpose Relays (12A @24VDC)
Dimensions:	252.0 x 147.4 x 55.0mm
IP protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	External Antenna on 3 metre cable (pre-fitted)
Operating radio frequency band:	433.075-434.775MHz

