

## ProGrip10 Radio Remote Control

	<b>System Part Number: UBRF-PG10-10</b>
	Radio Remote Control System consisting of ProGrip10 Radio Transmitter & DC10 Radio Receiver Unit with N/O Momentary Relay Outputs. AC Transmitter Charger included.

Standard System Package: (Customised label options available for ProGrip Transmitter to include button functions and company logo. Protective Bumper can also be supplied in Yellow, Green or Grey)

**1 x UBRF-PG10-10 includes:**

<b>UB/PRO10/433/TX01</b> 	<b>UB/RX/DC10/401</b> 	<b>PA31/CHARGER/01</b> 
----------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------

<b><u>UBRF-PG10-10</u></b>	<b>ProGrip10 Radio Remote Control System</b>	
<b><u>UB/PRO10/433/TX01</u></b>	<b>ProGrip10 Radio Transmitter</b>	
<b><u>PA31/CHARGER/01</u></b>	<b>AC Transmitter Charger (DC optional)</b>	
<b><u>UB/RX/DC10/401</u></b>	<b>DC10 Radio Receiver Unit</b>	

**Optional Accessories:**

<b><u>PA31/CHARGER/02</u></b>	<b>DC Transmitter Charger</b>	
<b><u>PA08/BOP/005</u></b>	<b>Lanyard Loop &amp; Lanyard for ProGrip</b>	
<b><u>PA08/BOP/006</u></b>	<b>Universal Belt-Clip for ProGrip</b>	
<b><u>PA08/BOP/013</u></b>	<b>Wall Holder for ProGrip</b>	

## Technical Specifications

### ProGrip10 Radio Transmitter

Number of buttons:	10
Battery type:	3 x AA (Rechargeable LiPo)
Dimensions:	159.4 x 77.9 x 35.5mm
Weight:	240g
IP Protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	Internal
Operating distance range:	Up to 150 metres
Operating radio frequency band:	433.075-434.775MHz

### DC10 Receiver Unit

Power supply:	12-24 VDC
Outputs:	10
Max voltage to contacts:	12A @ 250VAC & 24VDC
Dimensions:	201.0 x 122.4 x 55.0mm
IP protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	External Antenna on 3 metre cable (pre-fitted)
Operating radio frequency band:	433.075-434.775MHz

