

ProGrip8 Radio Remote Control

	<p>System Part Number: UBRF-PG8-10</p>
	<p>Radio Remote Control System consisting of ProGrip8 Radio Transmitter & DC10 Radio Receiver Unit with N/O Momentary Relay Outputs. AC Transmitter Charger included.</p>

Standard System Package: (Customised label options available for ProGrip8 Transmitter to include button functions and company logo. Protective Bumper can also be supplied in Yellow, Green or Grey)

1 x UBRF-PG8-10 includes:

<p>UB/PRO8/433/TX01</p> 	<p>UB/RX/DC10/401</p> 	<p>PA31/CHARGER/01</p> 
---	--	--

Part Numbers:

<u>UBRF-PG8-10</u>	ProGrip8 Radio Remote Control System	
<u>UB/PRO8/433/TX01</u>	ProGrip8 Radio Transmitter	
<u>PA31/CHARGER/01</u>	AC Transmitter Charger (DC optional)	
<u>UB/RX/DC10/401</u>	DC10 Radio Receiver Unit	

Optional Accessories:

<u>PA31/CHARGER/02</u>	DC Transmitter Charger	
<u>PA08/BOP/005</u>	Lanyard Loop & Lanyard for ProGrip	
<u>PA08/BOP/006</u>	Universal Belt-Clip for ProGrip	
<u>PA08/BOP/013</u>	Wall Holder for ProGrip	

Technical Specifications

ProGrip8 Radio Transmitter

Number of buttons:	8
Battery type:	3 x AA (Rechargeable LiPo)
Dimensions:	159.4 x 77.9 x 35.5mm
Weight:	240g
IP Protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	Internal
Operating distance range:	Up to 150 metres
Operating radio frequency band:	433.075-434.775MHz

DC10 Receiver Unit

Power supply:	12-24 VDC
Outputs:	10
Max voltage to contacts:	12A @ 250VAC & 24VDC
Dimensions:	201.0 x 122.4 x 55.0mm
IP protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	External Antenna on 3 metre cable (pre-fitted)
Operating radio frequency band:	433.075-434.775MHz

