ProGrip21 Infrared Remote Control

	System Part Number: **UBIR-PG21-26**
	Infrared Remote Control System consisting of ProGrip21 IR Transmitter & DC26 IR Receiver Unit with N/O Momentary Relay Outputs. AC Transmitter Charger included.

Standard System Package: (Customised label options available for ProGrip Transmitter to include button functions and company logo. Protective Bumper can also be supplied in Yellow, Green or Grey)

1 x UBIR-PG21-26 includes:

UB/PRO21/IR/TX01	UB/RX/DC26/IR01	PA31/CHARGER/01
		

Part Numbers:

UBIR-PG21-26	**ProGrip21 IR Remote Control System**	
UB/PRO21/IR/TX01	**ProGrip21 IR Transmitter**	
PA31/CHARGER/01	**AC Transmitter Charger (DC optional)**	
UB/RX/DC26/IR01	**DC26 IR Receiver Unit**	

Optional Accessories:

PA31/CHARGER/02	**DC Transmitter Charger**	
PA08/BOP/005	**Lanyard Loop & Lanyard for ProGrip**	
PA08/BOP/006	**Universal Belt-Clip for ProGrip**	
PA08/BOP/013	**Wall Holder for ProGrip**	

FSL Electronics Ltd
Unit 9 Kilcronagh Business Park, Cookstown BT80 9HJ
+44 (0)28 867 66131 | info@fslelectronics.com
FSLELECTRONICS.COM

Technical Specifications

ProGrip21 IR Transmitter

Number of buttons:	21
Battery type:	4 x AA (Rechargeable LiPo)
Dimensions:	209.3 x 98.0 x 34.8mm
Weight:	320g
IP Protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	N/A
Operating distance range:	Up to 30 metres line-of-sight
Operating Infrared frequency band:	36KHz PWM Infrared

DC26 IR Receiver Unit

Power supply:	12-24 VDC
Outputs:	26
Max voltage to contacts:	• 18 x General Purpose Relays (5A @24VDC) • 2 x Stop Relays (8A @24VDC) • 6 x General Purpose Relays (12A @24VDC)
Dimensions:	252.0 x 147.4 x 55.0mm
IP protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	N/A
Operating Infrared frequency band:	36KHz PWM Infrared



FSL Electronics Ltd
Unit 9 Kilcronagh Business Park, Cookstown BT80 9HJ
+44 (0)28 867 66131 | info@fslelectronics.com
FSLELECTRONICS.COM